15

20

1. An electro-optical device comprising light shielding portions comprising a lamination of a first colored layer and a second colored layer,

wherein at least one of the light shielding portions is formed overlapping at least a channel forming region of switching elements.

- 2. A device according to claim 1, wherein the first colored layer is blue.
- 3. A device according to claim 1, wherein the second colored layer is red.
- 4. A device according to claim 1, wherein the light shielding portion is provided on a substrate formed with said switching elements.
- 5. A device according to claim 1, wherein the light shielding portion is provided on an opposing substrate.
- 6. A device according to claim 1, wherein the electro-optical device is a transmission type liquid crystal display device in which the pixel electrode is made of a transparent conductive film.
- 7. A device according to claim 1, wherein the electro-optical device is a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player or an optical game machine.

10

15

20

8. An electro-optical device comprising:

a thin film transistor formed over a substrate; and

light shielding portions provided on an opposing substrate, said light shielding portions comprising a lamination of a first colored layer and a second colored layer,

wherein at least one of the light shielding portion is formed overlapping at least a channel forming region of the thin film transistor.

- 9. A device according to claim 8, wherein the first colored layer is blue.
- 10. A device according to claim 8, wherein the second colored layer is red.
- 11. A device according to claim 8, wherein the electro-optical device is a transmission type liquid crystal display device in which the pixel electrode is made of a transparent conductive film.
- 12. A device according to claim 8, wherein the electro-optical device is selected from the group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player or an optical game machine.
 - 13. An electro-optical device comprising:

a plurality of pixel electrodes; and

light shielding portions comprising a lamination of a first colored layer and

25 a second colored layer,

10

15

20

25

wherein the light shielding portions are formed so as to cover regions between each of said pixel electrodes and its adjacent pixel electrodes.

- 14. A device according to claim 13, wherein the first colored layer is blue.
- 15. A device according to claim 13, wherein the second colored layer is red.
- 16. A device according to claim 13, wherein the light shielding portions are provided on a substrate formed with switching elements connected to said pixel electrodes.
- 17. A device according to claim 13, wherein the light shielding portions are provided on an opposing substrate.
- 18. A device according to claim 13, wherein the electro-optical device is a transmission type liquid crystal display device in which the pixel electrode is made of a transparent conductive film.
- 19. A device according to claim 13, wherein the electro-optical device is selected from the group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player or an optical game machine.
- 20. A device according to claim 13, wherein said pixel electrodes connected a plurality of thin film transistor formed over a substrate, and wherein said the light



shielding portions are formed overlapping channel forming regions of the thin film transistors.